

Indoor

LUSID AIO X

Micro LED

**Superior display with Micro LED,
including touch options**

Higher screen quality, Improved
surfaced durability.



LUSID AIO X Specification

Product	AIO X 108" FHD	AIO X 135" FHD	AIO X 163" FHD	AIO 135" 4K	AIO X 163" 4K
Pixel pitch	1.25 mm	1.5625	1.875 mm	0.78125 mm	0.9375 mm
Brightness	600 nit	600 nit	600 nit	600 nit	600 nit
Screen size	108"	135"	163"	135"	163"
Screen dimension	2,400 x 1350 mm	3,000 x 1,687.5 mm	3,600 x 2,025 mm	3,000 x 1,687.5 mm	3,600 x 2,025 mm
Screen resolution	1,920 x 1,080 px	1,920 x 1,080 px	1,920 x 1,080 px	3,840 x 2,160 px	3,840 x 2,160 px
Refresh rate	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz
Viewing angle	178° (H, V)	178° (H, V)	178° (H, V)	178° (H, V)	178° (H, V)
Weight	135 kg	195 kg	260 kg	195 kg	260 kg
Maintenance	Front	Front	Front	Front	Front
Power consumption	Max. 0.8 kw/h, Avg. 0.3 kw/h	Max. 1.3 kw/h, Avg. 0.4 kw/h	Max. 1.8 kw/h, Avg. 0.6 kw/h	Max. 1.3 kw/h, Avg. 0.4 kw/h	Max. 1.8 kw/h, Avg. 0.6 kw/h
Life span	100,000 hours	100,000 hours	100,000 hours	100,000 hours	100,000 hours
Maintenance	Front				
Operating System	Android 11 (Optional)				
Video Input	HDMI 2.0 Input x3, HDMI 2.0 Output x1				
USB Input	USB 3.0 Type-A x2, USB 2.0 Type-A x1, USB 3.0 PH 2.0 (11-pin) x1				
Audio	3.5mm Audio Out x1, SPDIF (Optical) x1, Built-in Amplifier Audio Out x1 (2 × 20W)				
Network	Gigabit Ethernet (LAN) x1, Gigabit Ethernet (WAN) x1				
Speaker	30w x 2 (Optional)				