

Full Outdoor LCD Signage

QSR

TAA compliant product


QSR offers reliable outdoor displays with IP66 protection, meeting safety standards (UL and CE). They use IPS panels, reinforced glass, and adjust screen brightness based on surroundings for durability and image quality.

- IP 66 (65) rating
- Direct bonding
- IK10 tempered glass
- AR+AF coated display
- High brightness
- Auto brightness control




Direct Bonding

Combining LCD panels and tempered glass cover glass using transparent resin technology enhances color transmission, resulting in clearer picture quality.



Dual cooling

Faster and perfect heat dissipation with Dual Cooling



QSR specification

Product	32QSR	55QSR	55QSR Air	75QSR Air
Resolution	1920 x 1080	1920 x 1080	1920 x 1080	3840 x 2160
Brightness	2,000nit	2,500nit	2,500nit	3,000nit
Color Gamut	NTSC 72% (Typ.)	NTSC 72% (Typ.)	NTSC 72% (Typ.)	NTSC 68% (Typ.)
BLU Type	Edge	Edge	Edge	Direct
Panel Type	LG TNI	LG TNI (M+)	LG TNI (M+)	LG TNI (M+)
Surface Treatment	Anti-Reflection	Anti-Reflection	Anti-Reflection	Anti-Reflection
Optical Bonding	Yes	Yes	Yes	Yes
Outline Dimension	763.4 x 465.0 x 55.8mm	1271.6 x 743.1 x 47.1mm	1271.6 x 742.2 x 45.1mm	1723.6 x 1002 x 136.1mm
Weight	20.0kg	42.0kg	48.0kg	86kg
Power Consumption	120W (Max)	195W (Typ.)	220W (Typ.)	620W (Max)